

[Get a Quote](#)

Overview

Cisco CAB-CONSOLE-USB utilizes USB 2.0 to facilitate the console function. The USB A portion attaches to the USB port on your computer or laptop and the USB mini-B attaches to the device. This newer type of console cable is compatible with most newer Cisco equipment.

Quick Specification

SKU	CAB-CONSOLE-USB
Length	6 ft
Connector on First End	USB A
Connector on Second End	USB min-B
Cable Type	Console
Connectors	USB A - USB mini-B

Product Details:

The Front Panel:



Compare To Similar Items:

SKU	CAB-CONSOLE-USB	CAB-CONSOLE-RJ45
Product Type	Data Transfer Cable	Network Cable
Connector on First End	USB A	1 x RJ-45 Male
Connector on Second End	USB min-B	1 x RJ-45 Male Network
Conductor	Copper	Copper

Get more information:

Do you have any question about the CAB-CONSOLE-USB?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Type	USB cable
Length	6 ft
Connector	4 pin USB Type A - male
Connector (Second End)	Mini-USB Type B - male
Designed For	Cisco 1921, 1921 4-pair G.SHDSL bundle, 1921 ADSL2+ Annex M Bundle, 1921 ADSL2+ Bundle, 1921 SEC T1 Bundle, 1941, 1941 Mobile Wireless, 1941 Security, 1941 Security Bundle, 1941 SRE Bundle Cisco Catalyst 2960-24LC-S, 2960-24LT-L, 2960-24PC-L, 2960-24PC-S, 2960-24-S, 2960-24TC, 2960-24TC-L, 2960-24TC-S, 2960-24TT, 2960-48PST-L, 2960-48PST-S, 2960-48T, 2960-48TC, 2960-48TC-L, 2960-48TC-S, 2960-48TT, 2960-48TT-L, 2960-48TT-S, 2960-8TC, 2960-8TC-S, 2960G-24TC, 2960G-48TC, 2960G-8TC, 2960PD-8TT-L, 2960S-24PD-L, 2960S-24PS-L, 2960S-24TD-L, 2960S-24TS-L, 2960S-24TS-S, 2960S-48FPD-L, 2960S-48FPS-L, 2960S-48LPD-L, 2960S-48LPS-L, 2960S-48TD-L, 2960S-48TS-L, 2960S-48TS-S

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

