

[Get a Quote](#)

Overview

AIR-AP3802I-E-K9 is one of the Cisco 3800 Series Access Points. The Cisco Aironet 3800 Wi-Fi access points are designed for large enterprise organizations that rely on Wi-Fi to engage with customers. The 3800 series provides multiple gigabit uplink speeds of 2.5 Gbps and 5 Gbps in addition to 100-Mbps and 1-Gbps speeds. It also delivers new 802.11ac Wave 2 standard. Cisco Aironet 3800 Series Wi-Fi access points are highly versatile and deliver the most functionality of any access points in the industry. AIR-AP3802I-E-K9 is designed for Indoor, challenging environments, with internal antennas. Besides, it provides A regulatory domain.

Quick Specification

Product Code	AIR-AP3802I-E-K9
Antennas	Internal Antennas
Interfaces	<ul style="list-style-type: none">- 2 Ethernet ports- 100/1000/2500/5000 Multigigabit Ethernet (RJ-45)- CAT 5e cabling- Higher-quality 10GBASE-T (CAT 6/6a) cabling- 100/1000BASE-T autosensing (RJ-45 - AUX port)- Management console port (RJ-45)
Features	<ul style="list-style-type: none">- 4x4 MU-MIMO with three spatial streams- MRC- 802.11ac beamforming- 20-, 40-, 80, 160-MHz channels- PHY data rates up to 5.2 Gbps- Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx)- 802.11 DFS- CSD support
Regulatory Domain	<p>E (E regulatory domain):</p> <ul style="list-style-type: none">- 2.412 to 2.472 GHz; 13 channels- 5.180 to 5.320 GHz; 8 channels- 5.500 to 5.700 GHz; 8 channels <p>(excludes 5.600 to 5.640 GHz)</p>
System	<ul style="list-style-type: none">- 1024 MB DRAM- 256 MB flash
Dimensions (W x L x H)	8.66 x 8.68 x 2.46 in. (22 x 22 x 6.25 cm)
Net Weight	4.6 lb (2.09 kg)

Product Details:

The Front Panel:



Compare to Similar Items

Models	AIR-AP3802I-E-K9	AIR-AP3802E-E-K9
Antenna	Internal Antenna	External Antenna
Interfaces	<div>- 2 Ethernet ports</div> <div>- 100/1000/2500/5000 Multigigabit Ethernet (RJ-45)</div> <div>- CAT 5e cabling</div> <div>- Higher-quality 10GBASE-T (CAT 6/6a) cabling</div> <div>- 100/1000BASE-T autosensing (RJ-45 - AUX port)</div> <div>- Management console port (RJ-45)</div>	<div>- 2 Ethernet ports</div> <div>- 100/1000/2500/5000 Multigigabit Ethernet (RJ-45)</div> <div>- CAT 5e cabling</div> <div>- Higher-quality 10GBASE-T (CAT 6/6a) cabling</div> <div>- 100/1000BASE-T autosensing (RJ-45 - AUX port)</div> <div>- Management console port (RJ-45)</div>
Regulatory Domain	<div>E (E regulatory domain):</div> <div>- 2.412 to 2.472 GHz; 13 channels</div> <div>- 5.180 to 5.320 GHz; 8 channels</div> <div>- 5.500 to 5.700 GHz; 8 channels</div> <div>(excludes 5.600 to 5.640 GHz)</div>	<div>E (E regulatory domain):</div> <div>- 2.412 to 2.472 GHz; 13 channels</div> <div>- 5.180 to 5.320 GHz; 8 channels</div> <div>- 5.500 to 5.700 GHz; 8 channels</div> <div>(excludes 5.600 to 5.640 GHz)</div>

Get more information:

Do you have any question about the AIR-AP3802I-E-K9?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Detail	802.11ac Wave 2 AP w/CleanAir, 4x4:3, Mod, Internal Antenna, mGig, E Regulatory Domain
Regulatory Domain	E (E regulatory domain): - 2.412 to 2.472 GHz; 13 channels - 5.180 to 5.320 GHz; 8 channels - 5.500 to 5.700 GHz; 8 channels (excludes 5.600 to 5.640 GHz)
Software and supported wireless LAN controllers	Cisco Unified Wireless Network Software Release 8.2.MR1 or later Cisco 2500 Series Wireless Controllers, Cisco Wireless Controller Module for ISR G2, Cisco Wireless Services Module 2 (WiSM2) for Catalyst 6500 Series Switches, Cisco 5500 Series Wireless Controllers, Cisco Flex 7500 Series Wireless Controllers, Cisco 8500 Series Wireless Controllers, Cisco Virtual Wireless Controller Cisco IOS XE Software Release 16.3 – Target Q3 CY2016 Cisco Catalyst 3850 Series and 3650 Series Switches
802.11n version 2.0 (and related) capabilities	4x4 MIMO with three spatial streams Maximal ratio combining (MRC) 802.11n and 802.11a/g beamforming 20- and 40-MHz channels PHY data rates up to 450 Mbps (40 MHz with 5 GHz). Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx) 802.11 dynamic frequency selection (DFS) Cyclic shift diversity (CSD) support
802.11ac Wave 1 capabilities	4x4 MIMO with three spatial streams MRC 802.11ac beamforming 20-, 40-, and 80-MHz channels PHY data rates up to 1.3 Gbps (80 MHz in 5 GHz) Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx) 802.11 DFS CSD support
802.11ac Wave 2 capabilities	4x4 MU-MIMO with three spatial streams MRC 802.11ac beamforming 20-, 40-, 80, 160-MHz channels PHY data rates up to 5.2 Gbps Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx) 802.11 DFS CSD support
Integrated antenna	Flexible radio (either 2.4 GHz or 5 GHz) 2.4 GHz, gain 4 dBi, internal antenna, omnidirectional in azimuth 5 GHz, gain 6 dBi, internal directional antenna, elevation plane beamwidth 90° Dedicated 5-GHz radio 5 GHz, gain 5 dBi, internal antenna, omnidirectional in azimuth

AIR-AP3802I-E-K9 Datasheet



HI-NETWORK.com
Your Global Original Network Supplier

Interfaces	<ul style="list-style-type: none">◦ 2 Ethernet ports◦ 100/1000/2500/5000 Multigigabit Ethernet (RJ-45) – IEEE 802.3bz◦ CAT 5e cabling◦ Higher-quality 10GBASE-T (CAT 6/6a) cabling◦ 100/1000BASE-T autosensing (RJ-45 - AUX port)◦ Management console port (RJ-45)
Indicators	Status LED indicates boot loader status, association status, operating status, boot loader warnings, boot loader errors
Dimensions (W x L x H)	8.66 x 8.68 x 2.46 in. (22 x 22 x 6.25 cm),
Weight	4.6 lb (2.09 kg)
Input power requirements	802.3at PoE+, Cisco Universal Power over Ethernet (Cisco UPOE) 802.3at power injector (AIR-PWRINJ6=) 50W power supply (AIR-PWR-50=)
Power draw	30W at the PSE with all features enabled except for the USB 2.0 port 34W at the PSE with the USB 2.0 port enabled
Environmental	Cisco Aironet 3800i Nonoperating (storage) temperature: -22° to 158°F (-30° to 70°C) Nonoperating (storage) altitude test: 25°C, 15,000 ft. Operating temperature: 32° to 104°F (0° to 40°C) Operating humidity: 10% to 90% percent (noncondensing) Operating altitude test: 40°C, 9843 ft.
System memory	1024 MB DRAM 256 MB Flash
Warranty	Limited lifetime hardware warranty





Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223

