



## Overview

C9200L-48T-4X-E is the Catalyst 9200L 48-port Data 4x10G uplink Switch, with Network Essentials software. Cisco Catalyst 9200 Series switches extend the power of intent-based networking and Catalyst 9000 hardware and software innovation to a broader set of deployments. With its family pedigree, Catalyst 9200 Series switches offer simplicity without compromise it is secure, always on, and IT simplified.

## Quick Specification

Product Code	C9200L-48T-4X-E
Downlinks total 10/100/1000 or PoE+ copper ports	48 ports data
Uplink configuration	4x 10G fixed uplinks
Default primary AC power supply	PWR-C5-125WAC
Fans	Fixed redundant
Software	Network Essentials
Stack bandwidth	80 Gbps
DRAM	2 GB
Flash	4G
Switching capacity	176 Gbps
Forwarding rate	261.9 Mpps
Dimensions	1.73 x 17.5 x 11.3 in 4.4 x 44.5 x 28.8 cm



## Product Details:

### The Front Panel:



### The Back Panel:



### Catalyst 9200 series provides these highlights:

- Up to 48 ports of full Power over Ethernet Plus (PoE+) capability
- Resiliency with Field-Replaceable Units (FRU) and redundant power supply, fans, and modular uplinks
- Flexible downlink options with data or PoE+
- Operational efficiency with optional backplane stacking, supporting stacking bandwidth up to 160 Gbps
- UADP 2.0 Mini with integrated CPU offers customers optimized scale with better cost structure
- Enhanced security with AES-128 MACsec encryption, policy-based segmentation, and trustworthy systems
- Layer 3 capabilities, including OSPF, EIGRP, ISIS, RIP, and routed access
- Advanced network monitoring using Full Flexible NetFlow
- Cisco Software-Defined Access (SD-Access):
- Simplified operations and deployment with policy-based automation from edge to cloud managed with Cisco Identity Services Engine (ISE)

[Get a Quote](#)

- Network assurance and improved resolution time through Cisco DNA Center™
- Plug and Play (PnP) enabled: A simple, secure, unified, and integrated offering to ease new branch or campus device rollouts or updates to an existing network
- Cisco IOS XE: A Common Licensing based operating system for the enterprise Cisco Catalyst 9000 product family with support for model-driven programmability and streaming telemetry
- ASIC with programmable pipeline and micro-engine capabilities, along with template-based, configurable allocation of Layer 2 and Layer 3 forwarding, AccessControl Lists (ACLs), and Quality of Service (QoS) entries

## Accessories For C9200L:

### Modules and Cables:

Model	Description
C9200-STACK-KIT=	C9200 Stack Kit Spare
<a href="#">C9200L-STACK-KIT=</a>	C9200L Stack Kit Spare
STACK-T4-50CM	50CM Type 3 Stacking Cable
STACK-T4-1M	1M Type 3 Stacking Cable
STACK-T4-3M	3M Type 3 Stacking Cable
PWR-C5-125WAC/2=	125WAC power supply spare

### Compare To Similar Items:

Product number	Product description
<a href="#">C9200L-48T-4X-A</a>	Catalyst 9200L 48-port Data 4x10G uplink Switch, Network Advantage
<a href="#">C9200L-48T-4X-E</a>	Catalyst 9200L 48-port Data 4x10G uplink Switch, Network Essentials
<a href="#">C9200L-48P-4X-A</a>	Catalyst 9200L 48-port PoE+ 4x10G uplink Switch, Network Advantage
<a href="#">C9200L-48P-4X-E</a>	Catalyst 9200L 48-port PoE+ 4x10G uplink Switch, Network Essentials

Get more information:

Do you have any question about C9200L-48T-4X-E?

Contact us now via e-mail: [info@hi-network.com](mailto:info@hi-network.com)

## Specific Data Sheet:

Model	C9200L-48T-4X-E
Downlinks total 10/100/1000 or PoE+ copper ports	48 ports data

# C9200L-48T-4X-E Datasheet

Get a Quote



Uplink configuration	4x 10G fixed uplinks
Default primary AC power supply	PWR-C5-125WAC
Fans	Fixed redundant
Software	Network Essentials
Chassis Dimensions	1.73 x 17.5 x 11.3 in 4.4 x 44.5 x 28.8 cm
Virtual Networks	1
Stacking bandwidth	80 Gbps
Total number of MAC addresses	16,000
Total number of IPv4 routes (ARP plus learned routes)	11,000 (8,000 direct routes and 3,000 indirect routes)
IPv4 routing entries	3,000
IPv6 routing entries	1,500
Multicast routing scale	1,000
QoS scale entries	1,000
ACL scale entries	1,500
Packet buffer per SKU	6 MB buffers for 24- or 48-port Gigabit Ethernet models
Flexible NetFlow (FNF) entries	16,000 flows on 24- and 48-port Gigabit Ethernet models
DRAM	2 GB
Flash	4 GB
VLAN IDs	1024
Total Switched Virtual Interfaces (SVIs)	512
Jumbo frames	9198 bytes
Wireless bandwidth per switch	N/A
Switching capacity	176 Gbps
Forwarding rate	261.9 Mpps
Mean time between failures (hours)	503,400

Get a Quote

## Want to Buy

---

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

---

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: echo.hinetwork

WhatsApp Business: +8618057156223