

Get a Quote

Overview

2-Port Network Interface Module - FXS, FXS-E and DID NIM-2FXS is supporting for the Cisco 4000 ISR Series. The Cisco® 4000 Series Integrated Services Routers (ISRs) host the Cisco network interface modules (NIMs), which have evolved from the enhanced high-speed WAN interface card (EHWIC), increasing port density and module capability. Up to three integrated NIM slots on the 4000 Series allow for flexible configurations. The NIMs support online insertion and removal (OIR), reducing the downtime required for new or replacement modules.

Quick Specification

Product Number	NIM-2FXS
Product Description	2-Port Network Interface Module - FXS, FXS-E and DID
Number of Ports	2
Cisco IOS Release	XE3.13.4, XE3.14.3, XE3.15.1, XE3.16 and above
Weight	0.42 lb (191 g)

Product Details:

The Front Panel:



Accessories for NIM-2FXS:

Supported Devices:

Product number	Model	Description
Cisco ISR4321/K9	Cisco ISR 4321 (2GE,2NIM,4G FLASH,4G DRAM,IP Base)	50Mbps-100Mbps system throughput, 2 WAN/LAN ports, 1 SFP port, multi-Core CPU,2 NIM, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC
Cisco ISR4331/K9	Cisco ISR 4331 (2GE,2NIM,1SM,4G FLASH,4G DRAM,IP Base)	100Mbps-300Mbps system throughput, 2 WAN/LAN ports, 2 SFP ports, multi-Core CPU,1 service module slots, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC
Cisco ISR4351/K9	Cisco ISR 4351 (3GE,3NIM,2SM,4G FLASH,4G DRAM,IP Base)	200Mbps-400Mbps system throughput, 2 WAN/LAN ports, 3 SFP ports, multi-Core CPU,2 service module slots, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC
Cisco ISR4431/K9	Cisco ISR 4431 (4GE,3NIM,8G FLASH,4G DRAM,IP Base)	500Mbps-1Gbps system throughput, 4 WAN/LAN ports, 4 SFP ports, multi-Core CPU, Dual-power, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC, separate control data and services CPUs

Compare To Similar Items:

Product Number	NIM-2FXS/4FXO	NIM-2FXS
Product Description	2-Port FXS/FXS-E/DID and 4-Port FXO Network Interface Module	2-Port Network Interface Module - FXS, FXS-E and DID
Number of Ports	6	2
Cisco IOS Release	XE3.14.3, XE3.15.1, XE3.16 and above	XE3.13.4, XE3.14.3, XE3.15.1, XE3.16 and above
Weight	0.52 lb (236 g)	0.42 lb (191 g)

Get more information:

Do you have any question about the NIM-2FXS?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Product Number	NIM-2FXS
Product Description	2-Port Network Interface Module - FXS, FXS-E and DID
Number of Ports	2
Cisco IOS Release	XE3.13.4, XE3.14.3, XE3.15.1, XE3.16 and above
Weight	0.42 lb (191 g)

Telnet or console	Remote and local configuration, monitoring, and troubleshooting from Cisco IOS XE Software command-line interface.
Simple Network Management Protocol (SNMP)	<ul style="list-style-type: none">• Router and data service unit (DSU)/channel service unit (CSU) managed by single SNMP agent; router, DSU, and CSU appear as a single network entity to user• Standard MIB (MIB II)• Cisco Integrated DSU/CSU MIB• RFC 1406 T1 MIB, including Alarm Detection and Reporting
SNMP traps	Generated in response to alarms

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223