

[Get a Quote](#)

Overview

The 8-port Cisco® Gigabit Ethernet LAN Switch Network Interface Module (NIMs) NIM-ES2-8 can reduce your company's total cost of ownership (TCO) by integrating Gigabit Ethernet switch ports within Cisco 4000 Series Integrated Services Routers (ISRs). These low-density Gigabit Ethernet switches offer small to medium-sized businesses and enterprise branch offices a combination of switching and routing integrated into a single device.

Quick Specification

Product Code	NIM-ES2-8
Product Description	8-Port Layer 2 Gigabit Ethernet Switch Module NIM
Form Factor	Single-wide NIM form factor
Dimensions (H x W x D)	0.8 x 6.2 x 4.8 in. (2.1 x 18.8 x 12.2 cm)
Weight	108g (0.24 lb)

Product Details:

The Front Panel:



Accessories for NIM-ES2-8:

Platform Support:

Product number	Model	Description
CISCO ISR4221/K9	Cisco ISR 4221 (2GE,2NIM,4G FLASH,4G DRAM,IPB)	35Mbps-75Mbps system throughput, 2 WAN/LAN ports, 1 SFP port, multi-Core CPU,2 NIM
CISCO ISR4221-SEC/K9	Cisco ISR 4221 SEC Bundle with SEC lic	35Mbps-75Mbps system throughput, 2 WAN/LAN ports, 1 SFP port, multi-Core CPU,2 NIM, SEC Bundle with SEC lic
Cisco ISR4321/K9	Cisco ISR 4321 (2GE,2NIM,4G FLASH,4G DRAM,IP Base)	50Mbps-100Mbps system throughput, 2 WAN/LAN ports, 1 SFP port, multi-Core CPU,2 NIM, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC
Cisco ISR4331/K9	Cisco ISR 4331 (2GE,2NIM,1SM,4G FLASH,4G DRAM,IP Base)	100Mbps-300Mbps system throughput, 2 WAN/LAN ports, 2 SFP ports, multi-Core CPU,1 service module slots, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC
Cisco ISR4351/K9	Cisco ISR 4351 (3GE,3NIM,2SM,4G FLASH,4G DRAM,IP Base)	200Mbps-400Mbps system throughput, 2 WAN/LAN ports, 3 SFP ports, multi-Core CPU,2 service module slots, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC
Cisco ISR4431/K9	Cisco ISR 4431 (4GE,3NIM,8G FLASH,4G DRAM,IP Base)	500Mbps-1Gbps system throughput, 4 WAN/LAN ports, 4 SFP ports, multi-Core CPU, Dual-power, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC, separate control data and services CPUs

Compare To Similar Items:

Product Number	NIM-ES2-8	NIM-ES2-8-P
Product Description	8-Port Layer 2 Gigabit Ethernet Switch Module NIM	8-port PoE/PoE+ Layer 2 Gigabit Ethernet LAN Switch NIM
Supported Devices	Cisco 4000 Series Integrated Services Router	Cisco 4000 Series Integrated Services Router
Dimensions (H x W x D)	0.8 x 6.2 x 4.8 in. (2.1 x 18.8 x 12.2 cm)	0.8 x 6.2 x 4.8 in. (2.1 x 18.8 x 12.2 cm)
Weight	108g (0.24 lb)	149g (0.33 lb)

Get more information:

Do you have any question about the NIM-ES2-8?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Product Number	NIM-ES2-8
Product Description	8-Port Layer 2 Gigabit Ethernet Switch Module NIM

Form Factor	Single-wide NIM form factor	
Dimensions (H x W x D)	0.8 x 6.2 x 4.8 in. (2.1 x 18.8 x 12.2 cm)	
Weight	108g (0.24 lb)	
IEEE protocols	<ul style="list-style-type: none"> • Gigabit Ethernet: IEEE 802.3 and 10BASE-T • Gigabit Ethernet: IEEE 802.3u, 100BASE-TX, and 1000BASE-TX • IEEE 802.1d Spanning Tree Protocol • IEEE 802.1p CoS for Traffic Prioritization • IEEE 802.1q VLAN • IEEE 802.1X Security • IEEE 802.3x Full Duplex • IEEE 802.3af Power over Gigabit Ethernet Standard 	
RFC	RFC 2284, PPP Extensible Authentication Protocol (EAP)	
MIBs	<ul style="list-style-type: none"> • RFC 1213 • IF MIB • RFC 2037 ENTITY MIB • CISCO-CDP-MIB • CISCO-IMAGE-MIB • CISCO-FLASH-MIB • OLD-CISCO-CHASSIS-MIB • CISCO-VTP-MIB • CISCO-HSRP-MIB • OLD-CISCO-TS-MIB • CISCO-ENTITY-ASSET-MIB • CISCO-ENTITY-FRU-CONTROL-MIB • BRIDGE MIB (RFC 1493) 	<ul style="list-style-type: none"> • CISCO-VLAN-MEMBERSHIP-MIB • CISCO-VLAN-IFINDEX-RELATIONSHIP-MIB • RMON1-MIB • PIM-MIB • CISCO-STP-EXTENSIONS-MIB • OSPF MIB (RFC 1253) • IPMROUTE-MIB • CISCO-MEMORY-POOL-MIB • ETHER-LIKE-MIB (RFC 1643) • CISCO-ENTITY-FRU-CONTROL-MIB.my • CISCO-RTTMON-MIB • CISCO-PROCESS-MIB • CISCO-COPS-CLIENT-MIB
Manageability	<ul style="list-style-type: none"> • SNMP and Telnet interface support delivers comprehensive in-band management, and a CLI management console provides detailed out-of-band management. • An embedded RMON software agent supports four RMON groups (history, statistics, alarms, and events) for enhanced traffic management, monitoring, and analysis. • A SPAN port can mirror traffic from one or many ports to another port for monitoring all eight RMON groups with an RMON probe or network analyzer. • Trivial File Transfer Protocol (TFTP) reduces the cost of administering software upgrades by downloading from a centralized location. • Two LEDs per port provide convenient visual indication of the port link and PoE status. • Crash information support enables a switch to generate a crash file for improved troubleshooting. • Show-interface capabilities provide information about the configuration capabilities of any interface. 	
Connectors and cabling	<ul style="list-style-type: none"> • 10BASE-T ports: RJ-45 connectors, two-pair Category 3, 4, or 5 unshielded twisted pair (UTP) cabling • 100BASE-TX ports: RJ-45 connectors; two-pair Category 5 UTP cabling • 1000BASE-TX ports: RJ-45 connectors; two-pair Category 5e and Category 6 UTP cabling 	
LED indicators	<ul style="list-style-type: none"> • Link status LED: One LED per port for indicating link status • PoE LED: One LED per port system for PoE status indication 	
Internal power supply	Optional PoE system power supply available for all Cisco 4000 Series routers	
Internal redundant power supply	For the Cisco 4431 and 4451 routers only	

DC power support	<ul style="list-style-type: none"> • DC system power input available on the Cisco 4351, 4431, and 4451 routers • PoE option not available with DC system power input
Software support	Minimum Cisco IOS-XE Software Release 3.15 for Cisco 4000 Series routers: IP Base License of the Universal image
Operating temperature	32° to 104°F (0° to 40°C)
Operating humidity	10 to 90 percent, noncondensing
Nonoperating temperature	-4° to 149°F (-20° to 65°C)
Operating altitude	15,000 ft (4,570m)
Regulatory compliance, safety, and EMC	When installed in a Cisco 4000 Series router, the Cisco Gigabit Ethernet LAN Switch NIM meets the standards (regulatory compliance, safety, and EMC) of the router itself. Refer to the data sheets for the Cisco 4000 Series routers for more details.

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223