



Get a Quote

Overview

Cisco Catalyst 4507R+E chassis offers 7 slots with 5 line-card slots and 2 supervisor engine slots with support up to 244 ports and up to 1500W POE power per slot. Cisco Catalyst 4507R+E comprises evolutionary centralized modular architecture with exceptional functionality and flexibility. 1+1 supervisor engine redundancy with simultaneously supporting for classic and E-series line-cards in the same chassis delivers the low latency and high scalability network experience to ensure superior reliability for edging or core network. Any two Cisco Catalyst 4500E series Switches with Supervisor Engine 7L-E/7-E/8-E can be pooled together into a VSS, which doubles the system bandwidth, improves resiliency of the system and delivers the highest centralized reliable performance.

Quick Specification

| | |
|--------------------------|--|
| Product Code | WS-C4507R+E |
| Supervisor engine slot | 2 |
| Line-card slots | 5 |
| Redundant power supplies | 2 |
| Backplane | 48 Gbps full duplex per slot |
| Dimensions (H x W x D) | 48.74 x 43.97 x 31.70 cm |
| Rack Units (RU) | 11 RU |
| Weight | 20.19 kg |
| Airflow | Chassis fan tray: Right to left Power supply fan: Front to back |



Get a Quote



Product Details:

The Front Panel:



| | |
|---|--|
| ① | Power Supplies |
| ② | Switching modules (slots 1, 2, 5, 6, 7) |
| ③ | Supervisor engines (primary in slot 3 and secondary in slot 4) |
| ④ | Fan tray assembly |

Cisco Catalyst 4507R+E Switch Features

| Feature | Description |
|--------------------|--|
| Chassis | Three horizontal slots. Slots are numbered from 1 (top) to 7 (bottom). |
| Supervisor engines | Supports the following supervisor engines: - Supervisor Engine 8-E - Supervisor Engine 7L-E - Supervisor Engine 7-E |
| Modules | Supports up to 5 Catalyst 4500 series modules. |
| Backplane | 48 Gbps full duplex per slot |
| Fan tray | The chassis supports one hot-swappable fan tray. |
| Power supply | Supports one or two power supplies. All Catalyst 4500 series AC-input power supplies require single-phase source AC. |





Get a Quote

Accessories For WS-C4507R+E:

Recommended Elements:

| Category | Model | Description |
|-----------------------------|------------------|--|
| AP License | L-LIC-CTIOS-1A | 1 AP Adder License for the IOS based Wireless Controller (e-delivery) |
| Primary Supervisor | WS-X45-SUP8-E | Catalyst 4500 E-Series Supervisor 8-E |
| | WS-X45-SUP7-E | Catalyst 4500 E-Series Supervisor, 848Gbps |
| | WS-X45-SUP7L-E | Catalyst 4500 E-Series Supervisor LE, 520Gbps |
| 10/100/1000/MGig Line Cards | WS-X4748-RJ45-E | Cisco 4500 Line Card WS-X4748-RJ45-E Catalyst 4500 E-Series 48-Port 10/100/1000 Non-Blocking |
| | WS-X4748-UPOE+E | Cisco 4500 Line Card WS-X4748-UPOE+E Catalyst 4500E 48-Port UPOE 10/100/1000(RJ45) |
| | WS-X4748-RJ45V+E | Cisco 4500 Line Card WS-X4748-RJ45V+E Catalyst 4500E 48-Port PoE 802.3at 10/100/1000(RJ45) |
| 1 G Fiber Line Cards | WS-X4724-SFP-E | Catalyst 4500 E-Series 24-Port GE (SFP) |
| | WS-X4748-SFP-E | Catalyst 4500 E-Series 48-Port GE (SFP) |
| | WS-X4712-SFP-E | Catalyst 4500 E-Series 12-Port GE (SFP) |
| 10 G Fiber Line Cards | WS-X4606-X2-E | Catalyst 4500 E-Series 6-Port 10GbE (X2) |
| | WS-X4712-SFP+E | Catalyst 4500 E-Series 12-Port 10GbE (SFP+) |
| Power Supply | PWR-C45-1400AC | Catalyst 4500 1400W AC Power Supply (Data Only) |
| | PWR-C45-1400DC | C4500 1400W DC Triple Input SP Power Supply-data only |
| Supervisor Software License | L-C4500E-IP-ES= | Cisco Catalyst 4500E IP Base to Enterprise Services IOS upgrade license |

Compare To Similar Items:

| Model | WS-C4507R-E | WS-C4507R+E |
|--------------------------|--|--|
| Supervisor engine slot | 2 | 2 |
| Line-card slots | 5 | 5 |
| Redundant power supplies | 2 | 2 |
| Supervisor engines | - Supervisor Engine 8-E - Supervisor Engine 7L-E - Supervisor Engine 7-E | - Supervisor Engine 8-E - Supervisor Engine 7L-E - Supervisor Engine 7-E |
| Backplane | 24 Gbps full duplex per slot (240 Gbps) | 48 Gbps full duplex per slot |





Get a Quote

Get more information:

Do you have any question about WS-C4507R+E?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

| | |
|--|--|
| Model Name | WS-C4507R+E |
| Total number of slots | 7 |
| Line-card slots | 5 |
| Supervisor engine slots | 2 |
| Dedicated supervisor engine slot numbers | 3 and 4 |
| Supervisor engine redundancy | Yes |
| Supervisor engines supported | Supervisor Engines 8-E, 8L-E, 7-E, 7L-E, 6-E, and 6L-E |
| Maximum PoE per slot | 1500W |
| Bandwidth scalability per line-card slot | Up to 48 Gbps on all slots |
| Number of power supply bays | 2 |
| AC input power | Yes |
| DC input power | Yes |
| Integrated PoE | Yes |
| Minimum number of power supplies | 1 |
| Power supplies supported | 1000W AC 1400W AC 1300W ACV 2800W ACV 4200W ACV 6000W ACV 9000W ACV 1400W DC (triple input) 1400W-DC-P |
| Number of fan-tray bays | 1 |
| Location of 19-inch rack-mount | Front |
| Location of 23-inch rack-mount | Front (option) |
| Dimensions (H x W x D) | 19.19 x 17.31 x 12.50 in. (48.74 x 43.97 x 31.70 cm) |
| Rack units (RU) | 11RU |
| Chassis weight (with fan tray) | 44.50 lb (20.19 kg) |
| Mounting | 19- and 23-in. rack compatible (19-in. rack and cable guide hardware included) |



Get a Quote



Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

