

Overview

The Cisco C1300-8T-E-2G is a high-performance Ethernet switch designed to meet the rigorous needs of modern network environments. Featuring 8x 10/100/1000 ports and 2x Gigabit copper/SFP combo ports, this switch provides robust network connectivity, scalability, and flexibility. Ideal for small to medium-sized enterprises, the Cisco C1300-8T-E-2G ensures improved network efficiency and resilience.

Quick Specification

Table 1 shows the quick specification.

Model	C1300-8T-E-2G
Dimension	268 x 185 x 44 mm (10.56 x 7.28 x 1.73 in)
Weight	1.39 kg (3.06 lb)
Operating Temperature	23° to 122°F (-5° to 50°C)
Operating Humidity	10% to 90%, relative, noncondensing
Ports	8x 10/100/1000 ports
Combo Ports	2x Gigabit copper/SFP combo ports
Form Factor	Fixed Configuration

Figure 1 shows the appearance of C1300-8T-E-2G.



Product Details

Product Features

- High-performance 8x 10/100/1000 Ethernet ports for enhanced network capacity.
- 2x Gigabit copper/SFP combo ports for flexible uplink capabilities.
- Robust security features to protect against unauthorized access.
- Advanced Quality of Service (QoS) for prioritized network traffic handling.
- Easy-to-use management interface for seamless network administration.

Product Applications

- Small to medium-sized businesses needing reliable and scalable network infrastructure.
- Educational institutions requiring robust internal connectivity and data sharing capabilities.
- Healthcare facilities needing secure and fast data transmission between various departments.

Supported Options

Accessory	Model
SFP Module	GLC-LH-SMD
Power Adapter	PWR-ADPT
Mounting Bracket	BRKT-MNT

Compare to Similar Items

Model	Difference
Cisco C1200-24P-4X	24x 10/100/1000 ports, 4x 10 Gigabit SFP+ uplinks
Cisco C1000-16T-2G	16x 10/100/1000 ports, 2x Gigabit SFP uplinks
Cisco SG300-10	10x 10/100/1000 ports, no combo ports

Get More Information

Do you have any questions about the C1300-8T-E-2G?

Contact us now via info@hi-network.com.



Specification

C1300-8T-E-2G Datasheet	
Ports	8x 10/100/1000 ports
Combo Ports	2x Gigabit copper/SFP combo ports
Mounting	Rack-mountable
Forwarding Rate	14.88 Mpps
Switching Capacity	20.0 Gbps
Power	100-240V 50-60 Hz, external
Dimension	268 x 185 x 44 mm (10.56 x 7.28 x 1.73 in)
Weight	1.39 kg (3.06 lb)
Operating Temperature	23° to 122°F (-5° to 50°C)
Operating Humidity	10% to 90%, relative, noncondensing
Console port	Cisco standard RJ-45 console port and USB Type C port
USB port	USB Type C port on the front panel of the switch for easy file and image management as well as console port
Buttons	Reset button
Cabling type	Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T
LEDs	System, Link/Act, PoE, Speed
Flash	512 MB
CPU	ARM dual-core at 1.4 GHz
DRAM	1 GB DDR4
Certifications	UL (UL 62368), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A

Want to Buy

[Get a Quote](#)


[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)





Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223

