

Get a Quote

Overview

Cisco C9200L-48PXG-4X-E Switch is Catalyst 9200L 48-port 12xmGig, 36x1G, 4x10G PoE+, Network Essentials

Quick Specification

Model	C9200L-48PXG-4X-E
Downlinks total 10/100/1000 or PoE+ copper ports	48 ports full POE+ (12 mGig ports up to 10G, 36 ports up to 1G)
Uplink configuration	4x 10G fixed uplinks
Default primary AC power supply	PWR-C5-1KWAC
Fans	Fixed redundant
Software	Network Essentials
DRAM	2 GB
Flash	4 GB
VLAN IDs	1024

Product Details:

The Front Panel:



The Back Panel:



Accessories For C9200L-48PXG-4X-E:

Product Details:

StackWise-80 and StackWise-160 Kit and cables	
Product number	Product description
C9200-STACK-KIT=	C9200 Stack Kit Spare
C9200L-STACK-KIT=	C9200L Stack Kit Spare
STACK-T4-50CM	50CM Type 3 Stacking Cable
STACK-T4-1M	1M Type 3 Stacking Cable
STACK-T4-3M	3M Type 3 Stacking Cable
Power supplies	
Product Number	Product Description
PWR-C5-1KWAC/2=	1000WAC power supply spare

Get more information:

Do you have any question about the C9200L-48PXG-4X-E?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Downlinks total 10/100/1000 or PoE+ copper ports	48 ports full POE+ (12 mGig ports up to 10G, 36 ports up to 1G)
Uplink configuration	4x 10G fixed uplinks
Default primary AC power supply	PWR-C5-1KWAC
Fans	Fixed redundant
Software	Network Essentials
Chassis Dimensions	1.73 x 17.5 x 13.8 in
	4.4 x 44.5 x 35.0 cm
Virtual Networks	1
Stacking bandwidth	80 Gbps
Total number of MAC addresses	16,000
Total number of IPv4 routes (ARP plus learned routes)	11,000 (8,000 direct routes and 3,000 indirect routes)
IPv4 routing entries	3,000
IPv6 routing entries	1,500
Multicast routing scale	1,000
QoS scale entries	1,000
ACL scale entries	1,500
Packet buffer per SKU	6 MB buffers for 24- or 48-port Gigabit Ethernet models
Flexible NetFlow (FNF) entries	16,000 flows on 24- and 48-port Gigabit Ethernet models
DRAM	2 GB
Flash	4 GB
VLAN IDs	1024
Total Switched Virtual Interfaces (SVIs)	512
Jumbo frames	9198 bytes
Wireless bandwidth per switch	N/A
Switching capacity	392 Gbps
Forwarding rate	291.66 Mpps
Mean time between failures (hours)	337,360



Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223

