



Overview

The Cisco Unified SIP Phone 3905 is a cost-effective, entry-level IP phone that addresses the need for basic voice communications with common Cisco Unified Communications features in an attractive design that is also budget-friendly. The phone can fill the communication needs of cubicle, retail, classroom, manufacturing floor and hallway, as well as various wall-mounted deployments.

Quick Specification

Product Code	CP-3905
Protocols	SIP
Connectivity	10/100BASE-T wired Ethernet LAN port plus switched PC port.
Memory	<ul style="list-style-type: none">• 4-MB flash memory• 32-MB synchronous dynamic RAM (SDRAM)
Physical dimensions	8.07 x 5.91 x 2.11 in. (205 x 150 x 53.5 mm) (in slab mode with the foot stand folded)
Weight	20.96 oz (594.3g)
Power over Ethernet (PoE)	IEEE PoE 802.3af is supported, Class 1.



Get a Quote

Product Details:

The Front Panel:



Get more information:

Do you have any question about the Cisco IP Phone CP-3905?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Product Number	CP-3905
Protocols	SIP
Connectivity	10/100BASE-T wired Ethernet LAN port plus switched PC port.
Memory	<ul style="list-style-type: none"> • 4-MB flash memory • 32-MB synchronous dynamic RAM (SDRAM)
Language support	<p>Arabic (Arabic area), Bulgarian (Bulgaria), Catalan (Spain), Chinese (China), Chinese (Hong Kong), Chinese (Taiwan), Croatian (Croatia), Czech (Czech Republic), Danish (Denmark), Dutch (Netherlands), English (United Kingdom; prompts only), Estonian (Estonia), French (France), Finnish (Finland), German (Germany), Greek (Greece), Hebrew (Israel), Hungarian (Hungary), Italian (Italy), Japanese (Japan), Korean (Korea Republic), Latvian, Lithuanian, Norwegian (Norway), Polish (Poland), Portuguese (Portugal), Portuguese (Brazil), Romanian (Romania), Russian (Russian Federation), Spanish (Spain), Slovak (Slovakia), Swedish (Sweden), Serbian (Republic of Serbia), Serbian (Republic of Montenegro), Slovenian (Slovenia), Thai (Thailand), and Turkish (Turkey) are supported, but in different phases.</p>

Get a Quote

Physical dimensions	8.07 x 5.91 x 2.11 in. (205 x 150 x 53.5 mm) (in slab mode with the foot stand folded)
Weight	20.96 oz (594.3g)
Power over Ethernet (PoE)	IEEE PoE 802.3af is supported, Class 1.
Local power	The phone can also be powered locally with the power adapters.
Operational Temperature	32 to 104°F (0 ~ 40°C)
Relative Humidity	10 to 95% (noncondensing)
Storage Temperature	14 to 140°F (-10 to 60°C)
Cosmetic	Cisco Cosmetic Class B
Approvals and compliance	<p>Regulatory compliance:</p> <ul style="list-style-type: none"> • CE markings per directives 2004/108/EC and 2006/95/EC <p>Safety:</p> <ul style="list-style-type: none"> • UL 60950 Second Edition • CAN/CSA-C22.2 No. 60950 Second Edition • EN 60950 Second Edition • IEC 60950 Second Edition • AS/NZS 60950 • GB4943 <p>EMC:</p> <ul style="list-style-type: none"> • FCC Part 15 (CFR 47) Class B • ICES-003 Class B • EN55022 Class B • CISPR22 Class B • AS/NZS CISPR22 Class B • VCCI Class B • KN22 Class B • CISPR24 • EN55024 • EN61000-3-2 • EN61000-3-3 • KN 24 <p>Telecom:</p> <ul style="list-style-type: none"> • FCC Part 68 (47CFR) (HAC) • Canada-CS-03-HAC • Australia AS/ACIF S004, AS/ACIF S040 • New Zealand- PTC 220 Draft

Want to Buy

[Get a Quote](#)

[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223