

[Get a Quote](#)

## Overview

The industry-standard Cisco® Small Form-Factor Pluggable (SFP) Gigabit Interface Converter links your switches and routers to the network. The hot-swappable input/output device plugs into a Gigabit Ethernet port or slot. Optical and copper models can be used on a wide variety of Cisco products and intermixed in combinations of 1000BASE-T, 1000BASE-SX, 1000BASE-LX/LH, 1000BASE-EX, 1000BASE-ZX, or 1000BASE-BX10-D/U on a port-by-port basis. GLC-EX-SMD is 1000BASE-EX long-wavelength; with DOM.

## Quick Specification

Product Number	GLC-EX-SMD
Product Description	1000BASE-EX long-wavelength; with DOM
Wavelength (nm)	1310
Fiber Type	SMF
Operating Distance (m)	40,000 (131,234 ft)
Temperature Range	EXT
DOM Support	Yes

## Product Details:

### The Front Panel:



Get more information:

Do you have any question about the GLC-EX-SMD?

Contact us now via e-mail: [info@hi-network.com](mailto:info@hi-network.com)

## Specific Data Sheet:

Product Number	GLC-EX-SMD
Product Description	1000BASE-EX long-wavelength; with DOM
Wavelength (nm)	1310
Fiber Type	SMF
Operating Distance (m)	40,000 (131,234 ft)
Temperature Range	EXT
DOM Support	Yes

## Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: echo.hinetwork

WhatsApp Business: +8618057156223