

Get a Quote

Overview

The Cisco® Fourth-Generation 8-Port T1/E1 Multiflex Trunk Voice and WAN Network Interface Modules (NIMs) NIM-8MFT-T1/E1 supportS data and voice applications on the Cisco 4000 Integrated Services Routers. These cards combine WAN-interface-card (WIC), voice-interface-card (VIC), ISDN Primary Rate Interface (PRI), dial-access integration, and channelized-data (CE1T1) functions to provide superior flexibility, versatility, and investment protection through their many uses. Customers who choose to integrate data and voice in multiple steps preserve their investment in a T1/E1 WAN interface.

Quick Specification

Product Number	NIM-8MFT-T1/E1
Product Description	8 port Multi-flex Trunk Voice/Clear-channel Data T1/E1 Module
Number of Ports	8
Dimensions (H x W x D)	1.25 x 3.50 x 7.24 in. (3.18 x 8.89 x 18.39 cm)
Weight	0.52 lb (236g)

Product Details:

The Front Panel:



Accessories for NIM-8MFT-T1/E1:

Supported Devices:

Product number	Model	Description
Cisco ISR4321/K9	Cisco ISR 4321 (2GE,2NIM,4G FLASH,4G DRAM,IP Base)	50Mbps-100Mbps system throughput, 2 WAN/LAN ports, 1 SFP port, multi-Core CPU,2 NIM, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC
Cisco ISR4331/K9	Cisco ISR 4331 (2GE,2NIM,1SM,4G FLASH,4G DRAM,IP Base)	100Mbps-300Mbps system throughput, 2 WAN/LAN ports, 2 SFP ports, multi-Core CPU,1 service module slots, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC
Cisco ISR4351/K9	Cisco ISR 4351 (3GE,3NIM,2SM,4G FLASH,4G DRAM,IP Base)	200Mbps-400Mbps system throughput, 2 WAN/LAN ports, 3 SFP ports, multi-Core CPU,2 service module slots, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC
Cisco ISR4431/K9	Cisco ISR 4431 (4GE,3NIM,8G FLASH,4G DRAM,IP Base)	500Mbps-1Gbps system throughput, 4 WAN/LAN ports, 4 SFP ports, multi-Core CPU, Dual-power, Security, Voice, WAAS, Intelligent WAN, OnePK, AVC, separate control data and services CPUs

Compare To Similar Items:

Product Number	NIM-8MFT-T1/E1	NIM-2CE1T1-PRI
Product Description	8 port Multi-flex Trunk Voice/Clear-channel Data T1/E1 Module	2 port Multi-flex Trunk Voice/Channelized Data T1/E1 Module
Number of Ports	8	2
Dimensions (H x W x D)	1.25 x 3.50 x 7.24 in. (3.18 x 8.89 x 18.39 cm)	1.25 x 3.50 x 7.24 in. (3.18 x 8.89 x 18.39 cm)
Weight	0.52 lb (236g)	0.42 lb (191g)

Get more information:

Do you have any question about the NIM-8MFT-T1/E1?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Product Number	NIM-8MFT-T1/E1
Product Description	8 port Multi-flex Trunk Voice/Clear-channel Data T1/E1 Module
Number of Ports	8

Clear-Channel Data	Yes
MFT Packet Voice	Yes
Unstructured E1 (G.703) Support	No
Channelized Data	No
Dimensions (H x W x D)	1.25 x 3.50 x 7.24 in. (3.18 x 8.89 x 18.39 cm)
Weight	0.52 lb (236g)
Environmental	<ul style="list-style-type: none"> • Operating temperature: 0 to 50°C (32 to 122°F) • Storage temperature: -20 to +65°C (-4 to 148°F) • Relative humidity: 10 to 85% noncondensing operating; 5 to 95% noncondensing, nonoperating
T1 Compliance (partial list)	<ul style="list-style-type: none"> • TIA-968-A • CS-03 • Jate • ANSIT1.403
E1 Compliance (partial list)	<ul style="list-style-type: none"> • TBR4, TBR12, and TBR13 • ITU-T G.703, G.704, G.823, and I.431 • S016 (Australia)

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223