



[Get a Quote](#)

Overview

Cisco 10GBASE-LRM SFP+ transceiver module for MMF and SMF, 1310-nm wavelength, 220m, LC duplex connector.

Quick Specification

Product Code	SFP-10G-LRM
Device Type	Plug-in module
Form Factor	SFP+
Data Rate	10.3Gbps
Wavelength	1310nm
Power Budget	3.4dB
Max Reach Distance	220m
Transmit Power	-6.5~-0.5dBm
Receive Sensitivity	-12dBm
Voltage	3.3V
Power Consumption	1W
Connector	Dual LC
Fiber Type	MMF
Operation Temperature	0~70° C
DDMI	With
Application	10 Gigabit Ethernet



Product Details:

The Front Panel:



Get more information:

Do you have any question about the SFP-10G-LRM?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Product Name	SFP-10G-LRM
Device Type	SFP+ transceiver module
Form Factor	Plug-in module
Connectivity Technology	Wired
Cabling Type	10GBase-LRM
Data Link Protocol	10 GigE
Data Transfer Rate	10 Gbps
Optical Wave Length	1310 nm
Max Transfer Distance	984 ft
Compliant Standards	IEEE 802.3ae
Interfaces	1 x Ethernet 10GBase-LRM - LC/PC x 2
Compatible Slots	1 x SFP+
Width	0.5 in
Depth	2.2 in
Height	0.4 in



Weight	2.65 oz
Service & Support	Limited warranty - 90 days
Min Operating Temperature	32 °F
Max Operating Temperature	158 °F
Designed For	P/N: A9K-16T/8-B, A9K-16T/8-B=, ME-3600X-24FS-M, ME-3600X-24FS-M=, ME-3600X-24TS-M, ME-3600X-24TS-M=, ME-3800X-24FS-M, N7K-F132XP-15, N7K-F132XP-15=, N7K-M132XP-12L, N7K-M132XP-12L=, WS-C4948E-E, WS-C4948E-F, WS-C4948E-S, WS-X45-SUP7-E, WS-X45-SUP7-E/2, WS-X45-SUP7-E=, WS-X45-SUP7L-E, WS-X45-SUP7L-E/2, WS-X45-SUP7L-E=, WS-X4712-SFP+E, WS-X4712-SFP+E=

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

