



Get a Quote

Overview

Cisco Catalyst 3560 Series is a line of fixed-configuration, enterprise-class switches that include IEEE 802.3af and Cisco prestandard Power over Ethernet (PoE) functionality in Fast Ethernet and Gigabit Ethernet configurations. The Cisco Catalyst 3560 is an ideal access layer switch for small enterprise LAN access or branch-office environments, combining both 10/100/1000 and PoE configurations for maximum productivity and investment protection while enabling the deployment of new applications such as IP telephony, wireless access, video surveillance, building management systems, and remote video kiosks.

- 48 Ethernet 10/100/1000 ports and 4 SFP-based Gigabit Ethernet ports
- 1RU fixed-configuration, multilayer switch
- Enterprise-class intelligent services delivered to the network edge
- IP Base software feature set (IPB)

Quick Specification

Product Code	WS-C3560G-48TS-S
Type	Fixed
Topology	Ethernet (10/100/1000 Ethernet PortsBaseT) Gigabit Ethernet (SFP)
Maximum Port density	48 10/100/1000 Ethernet Ports ports
Uplinks	4 SFP ports
Modular/Expansion Slots	n/a
Architecture	Layer 2 Switching (basic connectivity), Layer 2 Switching (intelligent services), Layer 3 Switching, Voice Enabled
Form Factor	Fixed, Rack Mountable, Standalone/Clustering
Dimensions	1.73 x 17.5 x 16.1 in.
DRAM	128 MB





[Get a Quote](#)

Product Details:

The Front Panel:



The Back Panel:



Get more information:

Do you have any question about the WS-C3560G-48TS-S?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Manufacturer Name	WS-C3560G-48TS-S
Type	Fixed
Topology	Ethernet (10/100/1000 Ethernet PortsBaseT) Gigabit Ethernet (SFP)
Maximum Port density	48 10/100/1000 Ethernet Ports ports
Uplinks	4 SFP ports
Modular/Expansion Slots	n/a



[Get a Quote](#)

Architecture	Layer 2 Switching (basic connectivity), Layer 2 Switching (intelligent services), Layer 3 Switching, Voice Enabled
Form Factor	Fixed, Rack Mountable, Standalone/Clustering
Dimensions	1.73 x 17.5 x 16.1 in.
DRAM	128 MB
Hardware Redundancy	External Redundant Power Supply
High Availability/Resiliency	PVST, Broadcast Suppression, Unicast Suppression, Multicast Suppression, Spanning Tree, Portfast, Uplink Fast, Backbone Fast, 802.1s, 802.1w, HSRP
Management features	SPAN, RSPAN, CiscoView, Cisco Discover Protocol (CDP), Virtual Trunking Protocol (VTP), Telnet Client, BOOTP, TFTP, CiscoWorks, CWSI, RMON, SNMP, Clustering, Web-Based Management
Scalability	
WAN Interface Support	n/a
Throughput	38.7 Mpps
Backplane Capacity	32 Gbps
Number of VLANs	4k, 1024

Want to Buy

[Get a Quote](#)



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223