



Get a Quote

Overview

Cisco next generation Catalyst WS-C3850-24XS-S is stackable enterprise level switch and integrated with 24 ports of SFP+ 10G Ethernet fiber connection with Flexible Netflow feature.

Quick Specification

Product Code	WS-C3850-24XS-S
Enclosure Type	1RU
Feature Set	IP Base
Network SFP uplink module selection	C3850-NM-4-10G、3850-NM-8-10G、3850-NM-2-40G
Ports	24 x 10/100/1000 10G SFP+ Optical ports
Maximum stacking number	9
Stack bandwidth	480 Gpbs
RAM	4 GB
Flash Memory	4 GB
Dimensions	4.45 cm x 44.5 cm x 45.0 cm



Get a Quote


Product Details:

The Front Panel:



①	UID (blue beacon)
②	Mode button
③	Status LEDs
④	USB mini-Type B (console) port
⑤	USB Type A storage port
⑥	24 × 10/100/1000 10G SFP+ Optical ports
⑦	Network SFP uplink module slot

The Other Panel:





Get a Quote

①	Ground connector
②	CONSOLE (RJ-45 console port)
③	StackWise port connector
④	StackPower connector
⑤	Power supply modules
⑥	Fan modules
⑦	MGMT port
⑧	Reset Button

Accessories For WS-C3850:

Modules and Cables:

Part number	Description
C3850-NM-4-10G	Cisco 3850 Series 4 x 10GE Network Module
C3850-NM-8-10G	Cisco 3850 Series Network Module C3850-NM-8-10G 8 x 10GE Network Module
L-C3850-24-S-E=	C3850-24 IP Base to IP Services Electronic RTU License
PWR-C1-715WAC	Cisco 3850 Series Power Supply 350W AC
STACK-T1-50CM=	Cisco StackWise-480 50cm stacking cable for Cisco Catalyst 3850 series switch
STACK-T1-1M=	Cisco StackWise-480 1m stacking cable for Cisco Catalyst 3850 series switch

Compare to Similar Items

Models	WS-C3850-24XS-S	WS-C3850-24S-S
Feature Set	IP Base	IP Base
Network SFP uplink module	C3850-NM-4-10G C3850-NM-8-10G C3850-NM-2-40G	C3850-NM-4-1G C3850-NM-2-10G
Ports	24 × 10/100/1000 10G SFP+ Optical ports	24 × 10/100/1000 SFP Optical ports

Get more information:

Do you have any question about WS-C3850-24XS-S?

Contact us now via e-mail: info@hi-network.com



Get a Quote

Specific Data Sheet:

Model	WS-C3850-24XS-S
Enclosure type	Rack-mountable – 1U
Ports	24 x SFP+ ports
Network management Interface	Ethernet management port: RJ-45 connectors, 4-pair Cat-5 UTP cabling Management console port: RJ-45-to-DB9 cable for PC connections
Available PoE Power	None
Switching Capacity	320 Gbps
Maximum stacking number	up to 9 switches with same IOS feature set in same series
Stack Bandwidth	480 Gbps
Forwarding Performance	454.55Mpps
FNF entries	48,000 flows
Maximum VLANs IDs	1000
Maximum VLANs IDs	32K
CPU	Multicore CPU
RAM	4 G
Flash Memory	4 G
Number of AP per switch/stack	100
Number of wireless clients per switch/stack	2000
Total number of WLANs per switch	64
Wireless bandwidth per switch	up to 20 Gbps
Supported Aironet AP series	3600, 3500, 2600, 1600, 1260, 1140, 1040
Console ports	USB (Type-B), Ethernet (RJ-45)
Expansion Slot(s)	1 network module slot and 1 power redundant slot
Network Modules Selection	<ul style="list-style-type: none"> ● C3850-NM-4-1G: 4 x 1G uplinks network module ● C3850-NM-2-10G: 2 x 10G or 4 x 1G uplinks network module
Stacking cable	<ul style="list-style-type: none"> ● STACK-T1-50CM StackWise stacking cable with a 0.5 m length ● STACK-T1-1M StackWise stacking cable with a 1.0 m length ● STACK-T1-3M StackWise stacking cable with a 3.0 m length
Stack Power Cable (recommended)	<ul style="list-style-type: none"> ● CAB-SPWR-30CM stack power cable with a 30CM length ● CAB-SPWR-150CM stack power cable with a 150CM length
Power supply	PWR-C1-715WAC
Power Device	Power supply – redundant – plug-in module
Power Redundancy	optional
Voltage range (Auto)	100V-240V



Get a Quote

Power Consumption of standalone (in Watts)	205.5 (max)
Width	17.5 Inches (44.5 cm)
Depth	17.7 Inches (45.0 cm)
Height	1.75 Inches (4.45 cm)
Weight	13.5 Pounds (6.1 Kg)
Rack Mounting Kit	optional
MTBF in hours	307,990
Compliant Standards	<ul style="list-style-type: none"> • IEEE 802.1D Spanning Tree Protocol • IEEE 802.1p CoS Prioritization • IEEE 802.1Q VLAN • IEEE 802.1s • IEEE 802.1w • IEEE 802.1X • IEEE 802.1X-Rev • IEEE 802.11 • IEEE 802.1ab (LLDP) • IEEE 802.3ad • IEEE 802.3x full duplex on 10BASE-T, 100BASE-TX, and 1000BASE-T ports • IEEE 802.3 10BASE-T • IEEE 802.3u 100BASE-TX • IEEE 802.3ab 1000BASE-T • IEEE 802.3z 1000BASE-X • RMON I and II standards • SNMP v1, v2c, and v3
System software	IOS IP Base (Upgradable)
EnergyWise license	ENERGY-MGMT, ENERGY-MGT-100-K9
Software license	<ul style="list-style-type: none"> • C3850-24-S-E: IP Base to IP Services RTU paper license • L-C3850-24-S-E: IP Base to IP Services RTU electronic license
Access Point Licenses	<ul style="list-style-type: none"> • L-LIC-CT3850-UPG: Primary upgrade license SKU for Cisco 3850 wireless controller (e-delivery) • L-LIC-CTIOS-1A: 1 access point adder license for Cisco IOS Software based wireless controller (e-delivery) • LIC-CT3850-UPG: Primary upgrade license SKU for Cisco 3850 wireless controller (paper license) • LIC-CTIOS-1A: 1 access point adder license for the Cisco IOS Software based wireless controller (paper license)
Features	<ul style="list-style-type: none"> • RPS Support • Jumbo Frames • VLANs • Voice Vlan • VTPv2 • CDPv2 • LLDP • 802.3ad LACP and PAgP • PVST/PVST+ • 802.1W/802.1S • Port Fast/Uplink Fast • Dynamic Trunking Protocol (DTP) • port CoS Trust and Override • Trusted Boundary • ACL Classification • Ingress Policing • Auto QoS • Per VLAN policies • 802.1p queues • Scheduling • Priority Queuing • Configure CoS Priority Queues • Configure CoS Priority Queues • Configure Queue Weights • Configure Buffers and Thresholds • Class & Policy Maps • Modify CoS





Get a Quote

	<p>and DSCP Mapping • Weighted Tail Drop • IGMPv1,v2,v3 and MLDv1, v2 • DHCP server • DSCP transparency</p> <p>• HSRP, VRRP, BGP • RIPv1, v2 EIGRP, PIM OSPF, OSPFv3, EIGRPv6, BGPv4, IS-ISv4 • VRF-lite • PIM-SM/DM,PIM sparse-dense mode, SSM • Flexible Netflow</p>
Advanced Network security	<p>• Port security • DHCP snooping • Dynamic ARP inspection (DAI) • IP source guard • The Unicast Reverse Path Forwarding (uRPF)</p> <p>• Bidirectional data support on a SPAN • User authentication</p> <p>• Private VLAN • Router and VLAN ACLs • complete identity and security</p> <p>• Multidomain authentication • MAC address notification</p> <p>• IGMP filtering • Cisco security VLAN ACL</p> <p>• Secure Shell (SSH) Protocol, Kerberos, and Simple Network Management Protocol Version 3 (SNMPv3)</p> <p>• Port-based ACLs • TrustSec SXP • IEEE 802.1ae</p> <p>• TACACS+ and RADIUS authentication • Cisco standard and extended IP security router ACLs</p> <p>• Bridge protocol data unit (BPDU) Guard</p> <p>• Spanning Tree Root Guard (STRG) • Wireless end-to-end security</p>
Technical Support and Services	<p>• Cisco SMARTnet Service • Cisco Smart Foundation Service</p> <p>• Cisco SP Base Service • Cisco Focused Technical Support Services</p>
Operating temperature up to 5000 ft (1500 m)	23°F to 113°F (-5°C to +45°C)
Operating temperature up to 10,000 ft (3000 m)	23°F to 104°F (-5°C to +40°C)
Short-term exception at sealevel with single fan failure	23°F to 113°F (-5°C to +45°C)
Short-term exception up to 5000 feet (1500 m)	23°F to 122°F (-5°C to 50°C)
Short-term exception up to 10,000 feet (3000 m)	23°F to 113°F (-5°C to 45°C)
Operating temperature up to 6000 ft (1800 m)	23°F to 113°F (-5°C to +45°C)
Operating temperature up to 10,000 ft (3000 m)	23°F to 104°F (-5°C to +40°C)
Operating temperature up to 13,000 ft (4000m)	23°F to 95°F (-5°C to 35°C)
Short-term exception up to 6,000 feet (1800 m)	23°F to 131°F (-5°C to +55°C)
Short-term exception up to 10,000 feet (3000 m)	23°F to 122°F (-5°C to +50°C)
Short-term exception up to 13,000 feet (4000 m)	23°F to 113°F (-5°C to +45°C)
Short-term exception at sealevel with single fan failure	23°F to 113°F (-5°C to +45°)
Storage environment	-40°F to 160°F (-40°C to 70°C)
Operating altitude	Up to 13,000 Feet (Up to 4000m)
Storage altitude	Up to 15,000 Feet (Up to 4573m)
Operating relative humidity	10% to 95% noncondensing
Storage relative humidity 5	10% to 95% noncondensing



Get a Quote

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223