

Get a Quote

Overview

Cisco XFP10GER-192IR-L Compatible 10GBASE-ER/EW and OC-192/STM-64 IR-2 XFP Transceiver Module (SMF, 1550nm, 40km, LC, DOM).

Main features of the Cisco XFP Module include:

- . Supports 10GBASE Ethernet and OC-192/STM-64 data rates
- . Hot-swappable input/output device plugs into a XFP port of a Cisco Systems® router to link the port with the network
- . Provides flexibility of interface choice
- . Supports “pay-as-you-populate” model
- . Supports the digital optical monitoring capability
- . Supports the Cisco quality identification (ID) feature that helps enable a Cisco switch or router to identify whether the module is a Cisco certified and tested XFP
- . Supports optical interoperability with respective Cisco 10GBASE XENPAK and X2, and SFP+ modules on the same link

Quick Specification

| | |
|-----------------------------|--|
| Product Code | XFP10GER-192IR-L |
| Description | Cisco Multirate 10GBASE-ER/-EW and OC-192/STM-64 IR-2 XFP Module for SMF, low power (2.5W) |
| Operating Temperature Range | COM |
| Power Consumption (W) | 2.5 |

Product Details:

The Front Panel:



Compare to Similar Items:

| | | |
|-----------------------------|--|--|
| Product Code | XFP10GER-192IR-L | XFP10GER-192IR+ |
| Description | Cisco Multirate 10GBASE-ER/-EW and OC-192/STM-64 IR-2 XFP Module for SMF, low power (2.5W) | Cisco Multirate 10GBASE-ER/-EW and OC-192/STM-64 IR-2 XFP Module for SMF |
| Operating Temperature Range | COM | COM |
| Power Consumption (W) | 2.5 | 3.5 |

Get more information:

Do you have any question about the XFP10GER-192IR-L?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

| | |
|-------------------------------|---|
| Product Code | XFP10GER-192IR-L |
| Device Type | XFP transceiver module |
| Form Factor | Plug-in module |
| Connectivity Technology | Wired |
| Cabling Type | 10GBase-ER, 10GBase-EW |
| Data Link Protocol | SONET/SDH, 10 GigE |
| Data Transfer Rate | 10 Gbps |
| Optical Wave Length | 1550 nm |
| Line Rate | OC-192/STM-64 |
| Max Transfer Distance | 24.9 miles |
| Features | PoS (Packet over SONET) |
| Compliant Standards | IEEE 802.3ae |
| Interfaces | 1 x Ethernet 10GBase-ER/10GBase-EW - LC single-mode x 2 |
| Compatible Slots | 1 x XFP |
| Compliant Standards | Laser Class 1, IEC 60825-1 |
| Power Consumption Operational | 3.5 Watt |
| Width | 0.7 in |
| Depth | 2.8 in |
| Height | 0.4 in |
| Weight | 10.58 oz |
| Min Operating Temperature | 32 °F |

| | |
|---------------------------|---|
| Max Operating Temperature | 158 °F |
| Designed For | Cisco 1-Port 10GE XFP Interface Module, CRS-1 Series 4-Port 10GE LAN/WAN-PHY Interface Module, CRS-1 Series 8-port 10GbE LAN/WAN-PHY Interface Module, CRS-3 14-Port 10GE LAN/WAN-PHY Interface Module, CRS-3 20-port 10GbE LAN/WAN-PHY Interface Module Cisco Ethernet Services Plus Extended Transport 20G Line Card, 40G Line Card Cisco Ethernet Services Plus Transport Extended Combination 20G Line Card for Carrier Ethernet, Extended Combination 20G Line Card with DFC3CXL for Carrier Ethernet, Extended Combination 40G Line Card for Carrier Ethernet, Line Card (LAN/WAN PHY, OTN/G.709) |

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/add?contact=echo.hinetwork)

WhatsApp Business: +8618057156223

