



Get a Quote

Overview

Huawei X2CS uplink board is 2-port 10GE optical card for Huawei MA5683T MA5680T

Quick Specification

Model	H801X2CS
Port	2 10 GE Uplink Port
Plug-in module	SFP+ module
Dimensions (W x D x H)	25,40 mm x 237,00 mm x 197,20 mm
Energy consumption	Static: 17.6 W Maximum: 18 W
Maximum frame size	2052 bytes
Operating temperature range	From -25°C to 65°C

Product Details:

The Front Panel:



Get a Quote

Product Details:

The interface module provides two 10GE external interfaces.

The synchronous Ethernet clock module extracts the clock signal from the 10GE signal and synchronizes it to the 8K clock of the main control board.

The power module provides working power for each functional module in the board.

The clock module provides working clocks for each function module in the board.

The control module is used to report the status information of the board and the manufacturing information, and provide interface information.

In addition, the control module also has the function of managing and alarming the information of each module in the board.

Get more information:

Do you have any question about H801X2CS?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Model	H801X2CS
Port	2 10GE Uplink Ports
Pluggable Module	SFP+ Module
Corresponding Control Board	SCUF/SCUN/SCUL/SCUH
Dimensions (mm)	25.40 (W) x 237.00 (D) x 197.20 (H)
Power Consumption	Static: 17.6 W
	Maximum: 18 W
Maximum Frame Size	2052 bytes. After jumbo frame function is enabled, a maximum of 9216 bytes can be supported
Operating temperature	-25°C to +65°C

Get a Quote

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223