



Get a Quote

Overview

Huawei MA5683T MA5680T 2-port 10GE optical uplink board

Quick Specification

Model	H802X2CS
Port	2 10GE Uplink Ports
Pluggable Module	SFP+ Module
Corresponding Control Board	SCUF/SCUN/SCUL/SCUH
Power Consumption	Static: 17.6 W Maximum: 18 W
Maximum Frame Size	2052 bytes. After jumbo frame function is enabled, a maximum of 9216 bytes can be supported
Operating temperature	-25°C to +65°C

Product Details:

The Front Panel:



Get more information:

Do you have any question about H802X2CS?





[Get a Quote](#)

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Model	H802X2CS
Description	2-port 10GE Uplink Interface Card,support Synce
Net Dimension (D*W*H mm)	237*25*197
Product Line	Enterprise Network
Product Family	Access Network
Sub Product Family	GigaCopper
Pluggable Module	SFP+ Module
Corresponding Control Board	SCUF/SCUN/SCUL/SCUH
Maximum Frame Size	2052 bytes. After jumbo frame function is enabled, a maximum of 9216 bytes can be supported
Operating temperature	-25°C to +65°C

Want to Buy

[Get a Quote](#)



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

